

DuploCOLL® 5009

Double-sided adhesive mounting tape with foam carrier and aggressive synthetic rubber adhesive

Product construction			
	Name	Colour	Thickness [mm]
Liner	Silicone paper	white	approx. 0,08
Adhesive covered side	Synthetic rubber		
Carrier	Polyethylene foam	white	approx. 1,00
Adhesive open side	Synthetic rubber		
Total thickness:			approx. 1,08

Product advantages

- Very high initial adhesion (tack)
- Good specific adhesion on covalent substrates such as polyethylene and polypropylene
- Excellent final adhesion
- Developed for interior applications
- The combination of a synthetic rubber and permanently resilient polyethylene foam guarantees a very good bonding even on rough and structured surfaces.

Main application fields

- Mounting of hook, holders and dispensers in the sanitary area
- Self-adhesive preparation of covalent plastics such as polyolefins and Teflon
- Bonding of displays and product samples

Product features

Applicability on

Initial adhesion	● ● ●	Foam	○ ○ ○
Final adhesion	● ● ●	Rubber	● ● ○
Dimensional stability	● ○ ○	Fabric	● ● ○
Adhesion on even surfaces	● ● ●	Glass/Ceramics	● ● ●
Adhesion on rough surfaces	● ● ●	Wood	● ● ●
Ageing resistance	● ● ○	High energy plastics: PVC, PC, ABS,...	● ● ●
Weathering resistance	● ○ ○	Low energy plastics: PE, PP,...	● ● ●
Chemical resistance	● ○ ○	Metal	● ● ●
Resistance to plasticizers	● ○ ○	Paper/Cardboard	● ● ●

● ● ● very suitable ● ● ○ suitable ● ○ ○ suitable with reductions ○ ○ ○ not suitable

Specific technical data*

Temperature range	-40 °C to +70 °C**
Peel strength on polypropylene after 24 h at room temperature	25 N/25 mm (foam rupture)


* Specific test results, statistically not approved.

** Reached temperature in a rising heat test.

DuploCOLL® 5009

Double-sided adhesive mounting tape with foam carrier and aggressive synthetic rubber adhesive

Technical Data		
Shear strength	on stainless steel at +23 °C +/- 2°C	100 N/625 mm ²
Peel strength 180°	on stainless steel at +23 °C +/- 2°C	(foam rupture)



Application	
Recommended application temperature	18 °C to 35 °C
Application guidelines	www.lohmann-tapes.com

Storage	
Adhesive tapes should be stored at room temperature and normal humidity (50-70 %).	
The storage stability is one year after delivery.	

Product presentation					
Converted product	Rolls			Spools	
Width [mm]	> 6	> 9		6 - 19	
Length [m]	50	100		750	
Max. log width: 1260 mm	Other dimensions, die-cuts and sheets on request.				

For mechanical mounting of this adhesive tape we also offer a wide range of application devices.

IMPORTANT NOTE

The physical characteristics contained in this data sheet represent typical or average values. All application related statements, information and recommendations herein are given to the best of our knowledge and practical experience. Many factors beyond our control and uniquely within buyer's knowledge and control can affect the use and performance of our tape in a particular application. EXCEPT AS EXPRESSIVELY AGREED IN WRITING WE DO NOT TAKE OVER ANY WARRANTY OR LIABILITY FOR THE SUITABILITY OR USABILITY OF OUR TAPES FOR CERTAIN PURPOSES AND APPLICATIONS RESULTING FROM BUYER'S SPECIAL USAGE OF THE TAPES. EXCEPT WHERE PROVIDED BY MANDATORY LEGAL PROVISIONS, WE WILL NOT BE LIABLE FOR ANY DIRECT OR INDIRECT MATERIAL OR IMMATERIAL LOSSES OR DAMAGES ARISING FROM THE USAGE OR APPLICATION OF OUR TAPES. Solely the buyer is responsible for determining the suitability of the specific tape for its use in connection with his method of application. Please consult our Technical Applications Department for specific advice.

Date of issue: June 2023

Lohmann GmbH & Co. KG
 Irlicher Strasse 55
 56567 Neuwied
 Germany
 Phone: + 49 (0) 26 31 34 - 0
 Fax: + 49 (0) 26 31 34 - 6661
 E-mail: info@lohmann-tapes.com



Concerning product safety (confirmation, conformity to guidelines, REACH, etc.) please use the following
 E-mail address: product.safety@lohmann-tapes.com